

#### **Product Bulletin**

Product Name: Aquastrip XCEL-WR Product Code: 2572019 Revision Date: December 20, 2023

# Aquastrip® XCEL-WR

Aquastrip XCEL-WR is an alkaline liquid concentrate paint stripper, which is used full strength at temperatures ranging from 100°F to 180°F to remove powder coat, epoxy and acrylic coatings from all metal types.

#### Aquastrip XCEL-WR does NOT contain NMP.

Aquastrip XCEL-WR is fast acting and free rinsing, which accommodates further processing or as an application as a final finish.

### **Features & Benefits**

Effective on both ferrous	Single product for various
and nonferrous metals	applications
Free of NMP, solvents,	Meets strict environmental
phenols and acids	regulations
Does not cause hydrogen	Retains integrity of metal parts
embrittlement	
Easily filtered	Extended bath life

# **Typical Applications**

- Used in regions with strict environmental regulation
- Removal of powder, lacquers, and urethane coatings
- Excellent choice for removing organic coating from aluminum

# **Operating Conditions**

#### (Soak tank)

(	
Concentration	Full strength
Temperatures	100°F – 180°F
Time	As required
Agitation	Recommended

## Tank Construction

Tanks should be used in reinforced polypropylene or 300 series stainless steel vessel.



#### **Product Bulletin**

Product Name: Aquastrip XCEL-WR Product Code: 2572019 Revision Date: December 20, 2023

### **Titration Method**

- Pipette 2 mL sample into a 250 mL Erlenmeyer flask containing 50 mL of distilled water.
- 2. Add 5 to 10 drops of Methyl Orange/Xylene Cyanole indicator and mix.
- 3. Titrate with 0.5 N Hydrochloric Acid to a purple endpoint.
- 4. Record mL used.

Calculation

Concentration = mL 0.5 N HCl x 9.508

## Caution

Before using this material, read and understand OSHA Safety Data Sheet for Aquastrip XCEL-WR. Specific instructions and precautions should be followed to assure correct use and personal safety.

# **Waste Disposal**

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

## Our People. Your Problem Solvers.

For more information on this process, please call us at 203.756.5521 or email: <a href="mailto:techservice@hubbardhall.com">techservice@hubbardhall.com</a>

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**<sup>136</sup>.

